POWERED STACKER 1,000 LBS

- Remote control, floor lock, and safety screen are standard on all models.
- With a minimally charged battery, unit can be used while recharging.
- Three light LED charge status indicator No extra cost.
- Easy to read illuminated battery status voltmeter No extra cost.

COUNTER-BALANCED FORK MODELS

- Loading and unloading trucks.
- Positioning dies.
- Feeding material to presses.
- 25" long forks.
- Order enough weight kits for your planned load.
- AC models not available.

P/N 261038


PCBFL-64-25 Model:


Lift Height: 64" 0.A.H 80" Weight: 530 lbs. Capacity: 1.000 lbs.

Load Center: 13"

* Counterweights are not included and must be installed prior to use. Order Required Counterweight Kit for your load.

P/N: 261042 Stacker Load: 400 lbs. Capacity: 668 lbs.





		l		
	_			

REPLACEMENT PARTS LIST 64"/68" LIFT 64/68" HYD. CYLINDER

BATTERY CABLE (NEG.)

BATTERY CABLE (POS.)

BATTERY CHARGER

HYDRAULIC HOSE

LIFT CHAIN ASS'Y

SHIM: FLOOR LOCK

FLOOR LOCK

SOLENOID

BOARD: INDICATOR LIGHT

REMOTE CONTROL ASS'Y

ROLLER CARRIER ASS'Y

WHEEL, 5x2 PHENOLIC

CASTER, 5x2 PHENOLIC

ROLLER: MAG PLATFORM

POWER UNIT BATTERY

VOLTMETER

SWITCH

1

1

1

1

1

1

1

1

1

1

1 1

1

1

2

2

1

4

051164

109111

109102

109104

052769

052770

109114

052762

125827

2

3

7

THIS DRAWING IN ALL PARTICULARS IS WESCO INDUSTRIAL PRODUCTS INC. PROPERTY. ALL RIGHTS OF DESIGN, INVENTION OR USE OF ARE RESERVED.

PRINT ISSUED APR. 02, 2007 WESCO MANUFACTURING ENGINEERING DEPARTMENT

	WESCO INDUSTRIAL PI		RODUCTS INC. PENNA. 19446			
2	PCBFL-64-25		DRAWN:			
2			CHECKED:			
2	TOLERANCE UNLESS	APP. ENGR.				
		CIMAL 2 PLACE DECIMAL	scale: 1" = 20"			
- [± 1/64 ± .005	5 ± .01				
	ANGULAR ± 1-1/2*	SHEET 1 OF 1	B− 261038 🗟			
	BREAK ALL SHARP EDGES AND REMOVE ALL BURRS		_ == : : : : [[[]			